



Technical Data Sheet

PRIMAL™ AS-8012

Styrene acrylic binder

Description

PRIMAL™ AS-8012 is an elastomeric styrene acrylic emulsion for waterproofing membranes with excellent adhesion, water and alkali resistance. PRIMAL™ AS-8012 was developed without the introduction of ammonia, Alkyl Phenyl Ethoxylates (APEO) surfactants, formaldehyde or formaldehyde generators. PRIMAL™ AS-8012 offers excellent cement and powder compatibility with a very good balance of mechanical properties. These features and a very low VOC content facilitate the formulation of high performance products that address stringent environmental standards.

Applications

- Cementitious waterproofing membrane
- Acrylic waterproofing membrane
- Caulks

Benefits

- Balanced mechanical properties
- Excellent waterproofer properties
- Better powder compatibility
- Achieve both high tensile strength and elongation in the formulation
- Good alkali resistance
- Improve formulation stability and workability
- APEO free

Physical Properties

Appearance	Off-white milky liquid
Solids (Wt. %)	56
pH	6.0
Density, g/mL	1.100
Brookfield Viscosity @ 25°C, cPs	<1100
Tg, °C (Calculated)	-8
(MFFT), °C	< 0

These properties are typical but should not be considered specifications. For detailed specification rates please consult the product Certificate of Analysis.

Health & Safety Considerations

Safety Data Sheets (SDS) is available from The Dow Chemical Company. SDS is provided to help customers satisfy their own handling, safety and disposal needs and those that may be required by locally applicable health and safety regulations. SDS is updated regularly, therefore, please request and review the most current SDS before handling or using any product. For further questions consult your Dow contact person.

Handling & Storage

PRIMAL™ AS-8012 should be stored at temperatures between 1°C and 49°C in tightly sealed containers. Avoid freezing of the material. Local legislation on storage must be followed.

We recommend using the product under safety precautions as described in the SDS. Avoid contact with eyes and skin. Large quantities should be handled in a correctly ventilated area. Material can create slippery conditions. As the product contains water corrosion-resistance equipment should be used for processing. Low shear pumps like diaphragm pumps should be used.

Product Stewardship

Dow has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis for our product stewardship philosophy by which we assess the safety, health and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our product stewardship program rests with each and every individual involved with Dow products – from the initial concept and research to manufacture, use, sale, disposal and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

For further information contact:
North America +800-783-825 (free)
Europa, India, Africa, Middle East:
+800-3-694-6367 (free)
America Latina: +55-11-5188-9000
Pacifico: +800-7776-7776 (free)

<http://www.dow.com>

Disclaimer: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted.

NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.



*Trademark of The Dow Chemical Company

Form No. 832-03039